

Rules of  
**Department of Economic  
Development**  
Division 40—Office of Athletics  
Chapter 6—Facilities

Title	Page
4 CSR 40-6.010 Facility and Equipment Requirements .....	3

**Title 4—DEPARTMENT OF  
ECONOMIC DEVELOPMENT  
Division 40—Office of Athletics  
Chapter 6—Facilities**

**4 CSR 40-6.010 Facility and Equipment  
Requirements**

*PURPOSE: The purpose of this rule is to define the minimum facility requirements for the conduct of a professional boxing, professional kickboxing, professional martial arts or wrestling contest, except where the context clearly requires otherwise.*

(1) The ring shall not be less than sixteen (16) nor more than twenty feet (20') inside the ropes. The apron of the ring floor shall extend beyond the ropes not less than two feet (2'). The ring shall not be more than four feet (4') above the floor of the building or grounds of an outdoor arena and shall be provided with suitable steps for the use of contestants, managers, seconds and officials.

(2) The ring shall be equipped with at least three (3) ropes and not more than four (4) ropes. The ropes shall be not less than one inch (1") in diameter. These ropes shall be manila ropes, synthetic, plastic rope or any similar material and shall not be made of metal of any type. All ropes shall be wrapped securely in soft material. If three (3) ropes are used they shall extend in triple parallel lines, two feet (2'), three feet (3') and four feet (4') above the ring floor. If four (4) ropes are used, the lower rope shall be eighteen inches (18") above the ring floor, the second rope thirty inches (30"), the third rope forty-two inches (42") and the fourth rope fifty-four inches (54") above the ring floor. The ring floor shall be padded with a one-inch (1") layer of Ensolite or foam rubber (or equivalent) which is placed on a one-inch (1") base of Celotex (building board). The padding shall be covered with canvas, duck or similar material tightly stretched and laced securely in place.

(3) Ring posts shall not be less than three inches (3") or more than four inches (4") in diameter, extending from the floor of the building to the height fifty-eight inches (58") above the ring floor. The ring posts shall not be closer than eighteen inches (18") to the ring ropes. The turnbuckles must be covered with a protective padding.

(4) The gong, bell, buzzer or horn which is used must be sufficiently loud so that the officials and contestants can hear it clearly. The ten (10)-second warning may be by whistle or buzzer.

(5) Spectator seats shall not be closer than eight feet (8') from the outside edge of the apron of the ring. A physical barrier shall be placed designating eight feet (8') from the ring. The ringside area shall be under the jurisdiction of the office for the use of designated working officials, contestants, their seconds, judges, referees, physicians, announcer and medical representatives. Promoters are responsible for seeing that the working area is controlled and free of nonessential individuals. The promoter is also responsible for ensuring that no person is smoking within eight feet (8') of the ring.

(6) All gloves will be furnished by the promoter and shall be new or in good condition.

(7) Promoters must have an extra set of gloves for each size glove used during the contest, to be used in case gloves are broken or in any way damaged during the course of a bout.

(8) Scales shall be furnished by the promoter and shall be thoroughly tested and approved by the inspector prior to use in connection with any contest.

*AUTHORITY: section 317.006, RSMo 2000.\* Original rule filed April 30, 1982, effective Sept. 11, 1982. Amended: Filed March 2, 1989, effective May 11, 1989. Rescinded and readopted: Filed Nov. 15, 2001, effective May 30, 2002.*

*\*Original authority: 317.006, RSMo 1983, amended 1996.*